



HI1631G

General description

HI1631G

Main colour: Black ceramic glass

Connected load: 7400 W

Product dimensions (HxWxD): 5,4 × 60 × 52 cm

Real Bridge™ induction, Easy Slide™ touch control, Auto pan detection, Pause function



**Real
Bridge™
induction**



**Easy Slide™
touch
control**



**Auto pan
detection**



**Pause
function**

Construction & Performance

- Cooktop material: Glass - ceramic
- Connected load: 7400 W
- Energy consumption in standby mode: 0,5 W
- All heating elements (number of): 4
- Power boost
- 4 induction heating zones Left front: FlexZone 20×20 cm, 2,1/3 kW, Right front: FlexZone 20×20 cm, 1,6/1,85 kW, Left rear: FlexZone 20×20 cm, 1,6/1,85 kW, Right rear: FlexZone 20×20 cm, 2,1/3 kW

Interaction & Control

- SliderTouch, control at your fingertips
- Possible to control via WiFi: Prepared

Design & integration

- Faceted side edges
- Niche dimensions min-max (HxWxD): 7,7 × 55,8-56 × 49 cm

Safety & Maintenance

- Residual heat indicator

Technical data

- Connected load: 7400 W
- Frequency: 50-60 Hz

Dimensions

- Product dimensions (HxWxD): 5,4 × 60 × 52 cm
- Net weight: 10,5 kg

Logistic information

- Dimensions of packed product (HxWxD): 18 × 65 × 72,5 cm
- Gross weight: 11 kg
- Product code: 730457
- EAN code: 3838782106958

